

## EL-G24E4TG

L2 스위치



방송통신위원회



INNOBIZ  
기술혁신형중소기업



EL-G24E4TG는 기가비트 이더넷 24포트를 다운링크로 제공하고 10 기가비트 SFP 4포트를 업링크로 제공하는 L2 스위치입니다.

### Feature

- o 10/100/1000Base-T \* 24, 1G/10GBase-R \* 4, Console \* 1
- o 128G Switching Capacity
- o IGMP Snooping 지원
- o IEEE802.3x Flow Control 지원
- o Static routing
- o Flow classification based on L2/L3 802.1P/DSCP priority re-labeling, SP, WRR and SP+WRR, Flow monitoring and flow shaping QoS 지원
- o IEEE 802.1D/1s/1w의 STP/RSTP/MSTP를 지원
- o Console, Telnet,SSH2.0, WEB Management, SNMP v1/v2/v3, RMON 지원

### Application


- o CCTV, ITV and Traffic control system
- o Campus Network
- o Community Network
- o Security system
- o Process control and monitoring system

## Specification

<b>Standard</b>	IEEE802.3i 10Base-T IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T IEEE802.3z 1000Base-X IEEE802.3ae 10GBase-R IEEE 802.3x
<b>Fixed port</b>	10/100/1000M Base-T * 24 1G/10G SFP+ * 4 Console * 1
<b>Switching Capacity</b>	128Gbps
<b>Forwarding Rate</b>	95.23Mpps
<b>FLASH / RAM</b>	16MB / 256MB
<b>Jumbo frame</b>	9.6K
<b>MAC table</b>	16K
<b>L3</b>	Static route for IPv4 and IPv6
<b>VLAN</b>	Port based VLAN (4K) GVRP IEEE802.1Q, QinQ
<b>Port Aggregation</b>	LACP
<b>Storm control</b>	Broadcast, Multicast, Unknown-unicast
<b>Spanning tree</b>	STP(IEEE802.1d) RSTP(IEEE802.1w) MSTP(IEEE802.1s)
<b>Multicast</b>	IGMP Snooping V1/V2/V3 MLD Snooping V1
<b>DHCP</b>	DHCP server/relay/client DHCP snooping/option82
<b>QoS</b>	Each port s 8 output queues MAC/IP/TCP/UDP/VLAN/COS/DSCP/TOS based QoS 802.1P/DSCP priority re-labeling Scheduling mechanism (SP, WRR, SP+WRR, Tail-Drop, WRED) Flow monitoring and traffic shaping
<b>ACL</b>	L2 to L4 packet filtering function ACL based on port and VLAN

<b>Security</b>	Port isolation Port security IP source guard IEEE 802.1x AAA & Radius MAC learning limit ARP inspection
<b>Management</b>	Console, Telnet, SSH v1/v2, Web, SNMP v1/v2/v3 , TFTP , RMON
<b>Power</b>	AC100~220VAC (auto-adaptable), 50-60Hz
<b>Environment</b>	Working temperature: 0-50°C Storage temperature: -20-70°C Humidity: 5-90% no condensation

## Dimension



4F, 2-dong, 234, Saneop-ro 155beon-gil, Gwonseon-gu, Suwon-si, Gyeonggi-do, Republic of Korea  
Tel : 031-257-7157 / Fax : 031-257-7159

E-mail : elimopt@elimopt.co.kr / Web : <http://www.elimopt.co.kr>